

UTP3700S SERIES		
DC POWER SUPPLY		
UTP3705S		
Features		UTP3705S
Output Voltage	Ch1, Ch2	0 ~ 32V
	Ch3	
Output Current	Ch1, Ch2	0 ~ 5A
	Ch3	
Overload Effect		CV $\leq 1 \times 10^{-4} + 2\text{mV}$, CC $\leq 2\text{mA}$
Ripple & Noise		CV $\leq 1\text{mVrms}$, CC $\leq 1\text{mArms}$
Regulation		CV -20mV (Typical Value), CC -50mA (Typical Value)
Tracking Error		$5 \times 10^{-3} + 2\text{mV}$
Reliability		MTBF (e): ≥ 2000 hours
Other Features		Triple Output, Series or Parallel Operation, Current Limitation Auto Switching Between

GENERAL CHARACTERISTICS	
Power	220V $\pm 10\%$, 50Hz $\pm 4\%$
Product Colour	Red and Grey
Product NetWeight	Around 4kg
Product Size	210mm x 152mm x 305mm
Standard Accessories	English Manual and Power Cord
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	600 x 380 x 245mm (0.056 CBM Per Export Carton)
Standard Carton GrossWeight	9.5kg